

Section 7 Springs, shock absorbers, wheels

Group 77 Wheels, tires, hubs

Wheel

	Wheel with aluminium rim	Wheel with steel rim
Dimensions	6.5Jx16x52.5	6.5Jx16x52.5
	6.5Jx16x43	6.5Jx16x43 6Jx15x46 4Bx16x25
Lateral runout, max.	0.4 mm (0.016")	0.6 mm (0.031")
Radial runout, maximum	0.4 mm (0.016")	0.5 mm (0.028")
Maximum lateral runout of the hub front, rear		0.020 mm

Tightening torques

Wheel studs

Stage 1	20 ± 5 Nm
Stage 2	85 ± 15

Tyre dimensions

195165R15 M+S (Q max 160km/h)
205/55 R 15 91 V M+S (Q max 160km/h)
205/55 R 16 91 V M+S (Q max 160km/h)
T125/85 R 16 99M T-spare

Air pressure

Air pressure applies to cold tyres: kPa (psi)					
Engine	Speed km/h (mph)	1-3 people		Full load	
		Front	Rear	Front	Rear
2.4i (170 hp) B5244S4	0 -160 (0 - 100)	210 (30)	210(30)	250 (36)	250(36)
	High speed driving: > 160 (> 100)	250 (36)	210 (30)	280(41)	250(36)
T5 (220 hp) B5243T3	0-160 (0-100)	210 (30)	210 (30)	250(36)	250(36)
	High speed driving: > 160 (> 100)	270(39)	220(32)	290(42)	250(36)
"T-spare" T125/80 R 17	0 - 80 (0 - 50)	420(61)	420(61)	420(61)	420(61)